




TECHNICAL SPECIFICATIONS

Model	T20 I	T21 I
Installation type		embedded
Microswitches for exchange	1	2
Contact ratings		10 A / 250V 
Protection class		IP54
Operating ambient temperature		-20°C ÷ +55°C

Model	Description	Item code
T20 I (*)	Key operated buttons	401014
T21 I (*)	Key operated buttons	401015
T21 IF (**)	Key operated buttons	401017

XK30

TECHNICAL SPECIFICATIONS

Model	XK30
Installation type	wall
Microswitches for exchange	2
Contact ratings	10 A / 250V~
Protection class	IP30

Compatible with European cylinder DIN 18252

Model	Description	Item code
XK30	Key selector with lever release	391456



XK10 B - XK11 B

TECHNICAL SPECIFICATIONS

Model	XK10 B	XK10 B INOX	XK11 B
Installation type	wall or on column installation	-	wall or on column installation
Microswitches for exchange	1	-	2
Contact ratings	100 mA	-	100 mA
Protection class	IP54	-	IP54
Operating ambient temperature	-20 °C +55 °C	-	-20 °C +55 °C
Dimensions (LxDxH)	72 x 35 x 100 mm	-	72 x 35 x 100 mm

Model	Description	Item code
XK10 B	Key operated button	401304
XK10 B INOX	INOX key and command button	401046
XK11 B	Key operated button	401305
XK11 B INOX	INOX key and command button	401047

Provided without lock

